

Ogi Drive

desk electric height adjustment



Technical Data

- Worktop - MFC 28 mm, ABS edge 2 mm;
- Twin-motor frame - electric height adjustment in the range of: - 650-1300 mm, steel, powder-coated, 3 profiles 50 × 50 mm, 55 × 55 mm and 60 × 60 mm, load 100 kg, telescopic leg; - 700-1200 mm, steel, powder-coated, 2 profiles 55 × 55 mm and 60 × 60 mm, load 100 kg, telescopic leg;
- Control panel (twin-motor frame) - stepless height adjustment: A - basic control panel, the sensitivity of the anti-collision system is set to Medium; B (option with extra charge) - up and down keypad with memory, the ability to change the sensitivity of the anti-collision system within 3 levels: Low, Medium, High; C (option with extra charge) - round control panel with memory, the ability to change the sensitivity of the anti-collision system within 3 levels: Low, Medium, High; mounted to the worktop;
- Technical specification of the frame: height adjustment - 40 mm/sec Super Soft Start-Stop, drive - 2 synchronised motors with microprocessor, work control sensor, noise level - < 48dB, anti-collision mechanism, Standards - EN 527-2, EU Directives - 206/95EC, UI508 1999, UL 1004 R7 06, WE DC 2004/108WE, power supply - 230V, 300W, power consumption on Standby - 0.3W;
- Foot - Basic - powder-coated metal or Pro (option with extra charge) - aluminum, powder-coated or polished; levelling feet - range 5 mm;
- Options with extra charge: grommet - 2 pcs, Ø 88 mm; mediabox M14H - plastic frame, 2 x RJ45 (class E, cat. 6); + 1 x USB + 1 x HDMI + 4 x 230V, dimensions: 305x155x150 mm, power cord: 2000 mm; mediabox M14 - plastic frame, 2 x RJ45 (class E, cat. 6); + 1 x USB + 4 x 230V, dimensions: 305x155x150 mm, power cord: 2000 mm; mediabox M071 - 1 x 230V + 1 x USB A charger + 1 x USB C charger, colours: black or white, mounted instead of the existing grommet Ø88 mm (PK80); top access M15 - plastic frame, dimensions: 292x112x18 mm; mediabox M04 - aluminium frame, 4 x 230V, 2 x RJ45, 1 x USB, power cord 2 m; mediabox M04H - aluminium frame, 4 x 230V, 2 x RJ45, 1 x USB, 1 x HDMI, power cord 2 m; top access M05 - aluminium frame;
- Edges can be attached using laser technology or PUR glue - please contact Customer Service if tender or project guidelines require laser edging;
- Made in Poland, EU

Selected configuration

Guarantee

.mdd products - 5 years.
Electrical components - 2 years.

Assembly manuals



Certificates



BOD527

Height: 700 - 1200 mm

Width: 1200 mm

Length: 700 mm

Colour of the tabletop: Honey oak

Colour of the top edging: Honey oak

Type of foot: Foot Basic

Colour of the supporting leg: Black semi-matt RAL 9005

Colour of the foot: Not applicable

Type of plug: EU plug

Cable management: No cable ways

Colour of mediabox / grommet: Not applicable

Type of control panel: Control panel

Sustainability

- VOC Testing – we make sure that our furniture is safe for both the environment and the users. Ogi desks are tested for the presence of Volatile Organic Compounds using the chamber method in accordance with PN-EN ISO 16000-9.
 - Formaldehyde Testing – to meet the highest standards, we are constantly improving our production methods and the raw materials used. The levels of formaldehyde emission in our desks are now significantly below the requirements in accordance with the PN-EN 717-1:2006.
 - Safety, strength and durability – we believe in creating durable and timeless furniture. All desks in the Ogi family comply with the PN-EN 527-2+A1:2019-08.
 - Sustainable production – we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the life cycle of Ogi desks through the Environmental Product Declaration (EPD).
-

Material composition & packaging

- MFC: 48%
- Steel: 46%
- Plastic: 2%
- Cardboard: 4%

*average values for a representative of the group.

Recycled content

43%

Recyclability

- Recycling: 50%
- Downcycling: 50%

*average values for a representative of the group.

Packaging

Materials: cardboard

Recyclability: 100%